

SIEMENS MAGNETOM Avanto syngo MR B15

\\USER\\INVESTIGATORS\\Ravi\\ADNI-phantom\\QC Phantom-Localizer

TA: 0:10 PAT: Off Voxel size: 1.9x1.5x8.0 mm Rel. SNR: 1.00 SIEMENS: gre

Properties		Base resolution	192
Prio Recon	Off	Phase resolution	75 %
Before measurement		Phase partial Fourier	Off
After measurement		Interpolation	Off
Load to viewer	On	PAT mode	None
Inline movie	Off	Matrix Coil Mode	Auto (CP)
Auto store images	On	Distortion Corr.	Off
Load to stamp segments	Off	Prescan Normalize	Off
Load images to graphic segments	Off	Normalize	On
Auto open inline display	Off	Raw filter	On
AutoAlign Spine	Off	Intensity	Weak
Start measurement without further preparation	Off	Slope	25
Wait for user to start	Off	Elliptical filter	Off
Start measurements	single	Geometry	
Routine		Multi-slice mode	Sequential
Slice group 1		Series	Ascending
Slices	1	Saturation mode	Standard
Dist. factor	20 %	Special sat.	None
Position	Isocenter	Set-n-Go Protocol	Off
Orientation	Sagittal	Table position	H
Phase enc. dir.	A >> P	Table position	0 mm
Rotation	0.00 deg	Inline Composing	Off
Slice group 2		System	
Slices	1	Body	Off
Dist. factor	20 %	HE1	On
Position	Isocenter	HE3	On
Orientation	Coronal	HE2	On
Phase enc. dir.	R >> L	HE4	On
Rotation	0.00 deg	Positioning mode	REF
Slice group 3		MSMA	S - C - T
Slices	1	Sagittal	R >> L
Dist. factor	20 %	Coronal	A >> P
Position	Isocenter	Transversal	F >> H
Orientation	Transversal	Save uncombined	Off
Phase enc. dir.	R >> L	Coil Combine Mode	Sum of Squares
Rotation	90.00 deg	Auto Coil Select	Default
Phase oversampling	0 %	Shim mode	Tune up
FoV read	280 mm	Adjust with body coil	Off
FoV phase	100.0 %	Confirm freq. adjustment	Off
Slice thickness	8.0 mm	Assume Silicone	Off
TR	20.0 ms	Ref. amplitude 1H	205.057 V
TE	5.00 ms	Adjustment Tolerance	Auto
Averages	1	Adjust volume	
Concatenations	3	Position	Isocenter
Filter	Raw filter, Normalize	Orientation	Transversal
Coil elements	HE1-4	Rotation	0.00 deg
Contrast		R >> L	350 mm
TD	0 ms	A >> P	263 mm
MTC	Off	F >> H	350 mm
Magn. preparation	None	Physio	
Flip angle	40 deg	1st Signal/Mode	None
Fat suppr.	None	Segments	1
Water suppr.	None	Tagging	None
SWI	Off	Dark blood	Off
Averaging mode	Short term	Resp. control	Off
Reconstruction	Magnitude	Inline	
Measurements	1	Subtract	Off
Multiple series	Each measurement	1/+	
Resolution			

SIEMENS MAGNETOM Avanto syngo MR B15

Liver registration	Off
Std-Dev-Sag	Off
Std-Dev-Cor	Off
Std-Dev-Tra	Off
Std-Dev-Time	Off
MIP-Sag	Off
MIP-Cor	Off
MIP-Tra	Off
MIP-Time	Off
Save original images	On

Wash - In	Off
Wash - Out	Off
TTP	Off
PEI	Off
MIP - time	Off

Sequence

Introduction	On
Dimension	2D
Phase stabilisation	Off
Asymmetric echo	Off
Contrasts	1
Bandwidth	180 Hz/Px
Flow comp.	No

RF pulse type	Normal
Gradient mode	Fast
Excitation	Slice-sel.
RF spoiling	On

SIEMENS MAGNETOM Avanto syngo MR B15

\USER\INVESTIGATORS\Ravi\ADNI-phantom\QC Phantom Sagittal MPRAGE

TA: 7:42 PAT: Off Voxel size: 1.3x1.3x1.3 mm Rel. SNR: 1.00 SIEMENS: tfl

Properties

Prio Recon	Off
Before measurement	
After measurement	
Load to viewer	On
Inline movie	Off
Auto store images	On
Load to stamp segments	Off
Load images to graphic segments	Off
Auto open inline display	Off
AutoAlign Spine	Off
Start measurement without further preparation	On
Wait for user to start	Off
Start measurements	single

Routine

Slab group 1	
Slabs	1
Dist. factor	50 %
Position	L0.8 A22.5 H9.3
Orientation	Sagittal
Phase enc. dir.	A >> P
Rotation	0.00 deg
Phase oversampling	0 %
Slice oversampling	20.0 %
Slices per slab	160
FoV read	240 mm
FoV phase	100.0 %
Slice thickness	1.30 mm
TR	2400 ms
TE	3.5 ms
Averages	1
Concatenations	1
Filter	None
Coil elements	HE1-4

Contrast

Magn. preparation	Non-sel. IR
TI	1000 ms
Flip angle	8 deg
Fat suppr.	None
Water suppr.	None
Averaging mode	Long term
Reconstruction	Magnitude
Measurements	1
Multiple series	Off

Resolution

Base resolution	192
Phase resolution	100 %
Slice resolution	100 %
Phase partial Fourier	Off
Slice partial Fourier	Off
Interpolation	Off
PAT mode	None
Matrix Coil Mode	Auto (CP)
Distortion Corr.	Off
Prescan Normalize	Off
Normalize	Off
Raw filter	Off
Elliptical filter	Off

Geometry

Multi-slice mode	Single shot
Series	Interleaved
Set-n-Go Protocol	Off
Table position	H
Table position	0 mm
Inline Composing	Off
System	
Body	Off
HE2	On
HE4	On
HE1	On
HE3	On
SP4	Off
SP2	Off
SP8	Off
SP6	Off
SP3	Off
SP1	Off
SP7	Off
SP5	Off
Positioning mode	REF
MSMA	S - C - T
Sagittal	R >> L
Coronal	A >> P
Transversal	F >> H
Save uncombined	Off
Coil Combine Mode	Sum of Squares
Auto Coil Select	Default
Shim mode	Standard
Adjust with body coil	Off
Confirm freq. adjustment	Off
Assume Silicone	Off
Ref. amplitude 1H	205.057 V
Adjustment Tolerance	Auto
Adjust volume	
Position	L0.8 A22.5 H9.3
Orientation	Sagittal
Rotation	0.00 deg
F >> H	240 mm
A >> P	240 mm
R >> L	208 mm
Physio	
1st Signal/Mode	None
Dark blood	Off
Resp. control	Off
Inline	
Subtract	Off
Std-Dev-Sag	Off
Std-Dev-Cor	Off
Std-Dev-Tra	Off
Std-Dev-Time	Off
MIP-Sag	Off
MIP-Cor	Off
MIP-Tra	Off
MIP-Time	Off
Save original images	On

SIEMENS MAGNETOM Avanto syngo MR B15

Sequence

Introduction	On
Dimension	3D
Elliptical scanning	Off
Asymmetric echo	Off
Bandwidth	180 Hz/Px
Flow comp.	No
Echo spacing	7.9 ms
RF pulse type	Fast
Gradient mode	Fast*
Excitation	Non-sel.
RF spoiling	On

SIEMENS MAGNETOM Avanto syngo MR B15

Table of contents

\USER

INVESTIGATORS

Ravi

ADNI-phantom

QC Phantom-Localizer

QC Phantom Sagittal MPRAGE